

PREPARED FOR: JARCO, INC.

===== SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION =====

PRODUCT NAME: SLIPSTREAMER M/C WINDSHIELD POLISH
 PRODUCT CODE: L-11802

MANUFACTURER'S NAME: BRIDGEVIEW AEROSOL, LLC
 ADDRESS : 8407 S. 77th Avenue
 Bridgeview, IL 60455

EMERGENCY PHONE : 708-598-7100
 INFORMATION PHONE : 708-598-7100

===== SECTION 2 - HAZARDS IDENTIFICATION =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITATION. EYES: LIQUID OR VAPOR CAN IRRITATE.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 CAN BE ABSORBED. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN TO CRACK, LEADING TO DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
 NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)
 ACUTE: EYE IRRITANT. SKIN IRRITANT. CHRONIC: UNKNOWN.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
 NONE KNOWN.

===== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @	TEMP	PERCENT
PETROLEUM DISTILLATE, VM&P NAPHTHA OSHA PEL: 300 PPM, ACGIH TLV: 300 PPM	64742-89-8	10	68	26
BUTANE OSHA PEL: 800 PPM, ACGIH TLV: 800 PPM	106-97-8	1640	68	9
PROPANE OSHA PEL: 1000 PPM, ACGIH TLV: ASPHYXIAN	74-98-6	6350	68	3

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== SECTION 4 - FIRST AID MEASURES =====

EMERGENCY AND FIRST AID PROCEDURES
 INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. SKIN: WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

===== SECTION 5 - FIRE FIGHTING MEASURES =====

FLASH POINT: -156 deg F METHOD USED: ESTIMATED
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 9.5

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES PREFERRED. WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS. LIQUID CONTENT OF CONTAINER WILL NOT SUPPORT COMBUSTION. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE READILY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION 6 - ACCIDENTAL RELEASE MEASURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

===== SECTION 7 - HANDLING AND STORAGE =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120 DEG F. DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK PIN, NAIL OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES. DO NOT TAKE INTERNALLY. SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

===== SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION =====

PRECAUTIONS

THE STORAGE OF NON-FLAMMABLE PRODUCTS WITH NON-FLAMMABLE OR FLAMMABLE PRESSURIZING AGENT, IN CARTONS, IS THE SAME AS FOR ORDINARY CANNED GOODS IN CARTONS.

RESPIRATORY PROTECTION

NONE UNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CONTAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION

SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

PROTECTIVE GLOVES

NONE UNDER NORMAL USE. SOLVENT RESISTANT REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

NONE UNDER NORMAL USE; HOWEVER, USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NONE UNDER NORMAL USE; HOWEVER, USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

===== SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES =====

BOILING RANGE: -44 deg F - 250 deg F SPECIFIC GRAVITY (H2O=1): 0.84
VAPOR DENSITY: UNKNOWN EVAPORATION RATE: UNKNOWN
SOLUBILITY IN WATER: COMPLETE
APPEARANCE AND ODOR: AEROSOL PRODUCT

===== SECTION 10 - STABILITY AND REACTIVITY =====

STABILITY: STABLE
CONDITIONS TO AVOID
APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID)
OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION 11 - TOXICOLOGICAL INFORMATION =====

LONG-TERM TOXICOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT.

===== SECTION 12 - ECOLOGICAL INFORMATION =====

LONG-TERM ECOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT.

===== SECTION 13 - DISPOSAL CONSIDERATIONS =====

WASTE DISPOSAL METHOD
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

===== SECTION 14 - TRANSPORT INFORMATION =====

BY LAND: DOT PROPER SHIPPING NAME: CONSUMER COMMODITY, ORM-D
BY WATER: DOT PROPER SHIPPING NAME: UN 1950, Aerosols, 2.1, LTD QTY
BY AIR: DOT PROPER SHIPPING NAME: UN1950, Aerosols, flammable, 2.1, LTD QTY
(Packing instruction Y203 applies)

===== SECTION 15 - REGULATORY INFORMATION =====

ALL INGREDIENTS ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE EXEMPT.

===== SECTION 16 - OTHER INFORMATION =====

DATE PRINTED: 06/18/09

NAME OF PREPARER: ESP

HMS CODES: H-1 F-2 R-0 P-

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.