

Printing date 06/27/2023

Reviewed on 06/27/2023

1 Identification

- · Product identifier
- · Trade name: Muc-Off Motorcycle Chain Cleaner
- Article number: 650, 650ES, 650US
- · Application of the substance / the mixture Cleaner solvent
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- Muc-Off Ltd

UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW EU-Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork, Ireland, T23 AT2P Tel: +44(0)1202 307790 Email: info@muc-off.com

- · Information department: Research & Development/E-mail: info@muc-off.com
- Emergency telephone number: CHEMTREC: 1-800-424-9300 24HR

*

2 Hazard(s) identification

Classification of the substance or mixture



Flammable Aerosols 1 H222 Extremely flammable aerosol.

GHS04 Gas cylinder

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

GHS08 Health hazard

Aspiration Hazard 1 H304

H304 May be fatal if swallowed and enters airways.

· Label elements

- GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:
- Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%
- · Hazard statements
- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.

Printing date 06/27/2023

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

	(Contd. of page 1
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection.
P312	Call a poison center/doctor if you feel unwell.
P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations
· Classific	cation system:
	atings (scale 0 - 4)
04	Health = 0 Fire = 4 Reactivity = 0
·WHMIS	S-ratings (scale 0 - 4)
HEALTH	• Health $= 0$
FIRE	4 Fire = 4
REACTIV	Reactivity = 3
	azards
· Other h	
00000	of PBT and vPvB assessment
• Results	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Cleansing agent

· Dangerou	is components:	
	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%	50-<75%
106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)	10-<25%
74-98-6	propane	10-<25%
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	1-<2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Water haze
- Fire-extinguishing powder
- Carbon dioxide
- Alcohol resistant foam
- · For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

[·]US

Printing date 06/27/2023

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

(Contd. of page 2) • Special hazards arising from the substance or mixture No further relevant information available. • Advice for firefighters

· Protective equipment: Mount respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

Trottetive	Action Criteria for Chemicais	
· PAC-1:		
106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)	5500* ppm
74-98-6	propane	5500* ppm
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	5500* ppm
140-11-4	140-11-4 benzyl acetate 5989-27-5 (R)-p-mentha-1,8-diene	
5989-27-5		
101-84-8	diphenyl ether	2 ppm
141-78-6	ethyl acetate	1,200 ppm
· PAC-2:		1
106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)	17000** ppm
74-98-6	propane	17000** ppm
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	17000** ppn
140-11-4	benzyl acetate	330 ppm
5989-27-5	(R)-p-mentha-1,8-diene	67 ppm
101-84-8	101-84-8 diphenyl ether 16	
141-78-6	ethyl acetate	1,700 ppm
· PAC-3:		
106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)	53000*** ppm
74-98-6	propane	33000*** ppm
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	53000*** ppm
140-11-4	benzyl acetate	2,000 ppm
5989-27-5	(R)-p-mentha-1,8-diene	170 ppm
101-84-8	diphenyl ether	96 ppm
141-78-6	ethyl acetate	10000** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

⁻⁻⁻⁻US

Printing date 06/27/2023

*

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

	(Contd. of page 2
	nation about protection against explosions and fires:
	t spray on a naked flame or any incandescent material. gnition sources away - Do not smoke.
	t against electrostatic charges.
	rized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric
	Do not pierce or burn, even after use.
	tions for safe storage, including any incompatibilities
· Stora	
	rements to be met by storerooms and receptacles: n a cool location.
	ve official regulations on storing packagings with pressurized containers.
	nation about storage in one common storage facility:
	ve official regulations on storing packagings with pressurized containers.
	er information about storage conditions: n cool, dry conditions in well sealed receptacles.
	t from heat and direct sunlight.
	ic end use(s) No further relevant information available.
RExno	sure controls/personal protection
-	
· Addit	ional information about design of technical systems: No further data; see section 7.
· Contr	ol parameters
	onents with limit values that require monitoring at the workplace:
The to	
	llowing constituents are the only constituents of the product which have a PEL, TLV or other
recom	mended exposure limit.
recom At thi	mended exposure limit. time, the remaining constituent has no known exposure limits.
recom At thi 106-9	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K)
recom At thi 106-9 REL	<pre>mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m³, 800 ppm</pre>
recom At thi 106-9 REL	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m³, 800 ppm Short-term value: 1000 ppm
recom At thi 106-9 REL TLV	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX)
recom At thi 106-9 REL TLV 74-98	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane
recom At thi 106-9 REL TLV 74-98 PEL	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm
recom At thi 106-9 REL TLV 74-98 PEL REL	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm
recom At thi 106-9 REL TLV 74-98 PEL REL TLV	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX)
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m³, 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m³, 1000 ppm Long-term value: 1800 mg/m³, 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm See Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX)
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX)
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV · Addit	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) onal information: The lists that were valid during the creation were used as basis. ure controls
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV • Addit • Expo • Perso	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) 5 isobutane information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment:
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV • Addit • Expos • Perso • Gener	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) onal information: The lists that were valid during the creation were used as basis. ure controls
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV • Addit • Expos • Genet Wash Do no	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. t inhale gases / fumes / aerosols.
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV * Addit * Expose * Gene Wash Do no Gener	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m³, 800 ppm Short-term value: 1000 ppm [EX) 6 propane Long-term value: 1800 mg/m³, 1000 ppm Long-term value: 1800 mg/m³, 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) fonal information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. t inhale gases / fumes / aerosols. al ventilation
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV 75-28 TLV * Addit • Expo • Gene Wash Do no Gener • Breat	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. t inhale gases / fumes / aerosols. al ventilation hing equipment:
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV 75-28 TLV * Addit • Expo • Cene Wash Do nc Gener Wash Do nc Gener	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm See Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. i inhale gases / fumes / aerosols. al ventilation hing equipment: itable respiratory protective device in case of insufficient ventilation.
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV 75-28 TLV * Addit • Expo • Cene Wash Do no Gener • Breat Use su Filter	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm See Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. i inhale gases / fumes / aerosols. al ventilation hing equipment: itable respiratory protective device in case of insufficient ventilation.
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV * Addit • Expo • Addit • Expo • Can • 	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. i inhale gases / fumes / aerosols. al ventilation hing equipment: itable respiratory protective device in case of insufficient ventilation. A2/P2
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV * Addit • Expo • Addit • Expo • Can • 	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. t inhale gases / fumes / aerosols. al ventilation bing equipment: itable respiratory protective device in case of insufficient ventilation. A2/P2 tion of hands:
recom At thi 106-9 REL TLV 74-98 PEL REL TLV 75-28 TLV * Addit • Expo • Addit • Expo • Can • 	mended exposure limit. time, the remaining constituent has no known exposure limits. 7-8 butane (containing < 0.1% butadiene (203-450-8), Note K) Long-term value: 1900 mg/m ³ , 800 ppm Short-term value: 1000 ppm (EX) 6 propane Long-term value: 1800 mg/m ³ , 1000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm see Appendix F Minimal oxygen content (D, EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) 5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Short-term value: 1000 ppm (EX) ional information: The lists that were valid during the creation were used as basis. ure controls nal protective equipment: al protective and hygienic measures: hands before breaks and at the end of work. t inhale gases / fumes / aerosols. al ventilation bing equipment: itable respiratory protective device in case of insufficient ventilation. A2/P2 tion of hands:

Printing date 06/27/2023

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

(Contd. of page 4)

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

· Penetration time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:
- Safety glasses



Tightly sealed goggles

· Body protection:

Use protective suit.

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

· Limitation and supervision of exposure into the environment

Use a suitable container to prevent environmental contamination.

Physical and chemical proper	
· Information on basic physical and c	hemical properties
· General Information	
· Appearance:	A 1
Form:	Aerosol
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44.5 °C (-48.1 °F)
· Flash point:	-97 °C (-142.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto igniting:	236 °C (456.8 °F)
[•] Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
· Vapor pressure at 20 °C (68 °F):	8300 hPa (6225.5 mm Hg)
· Density at 20 °C (68 °F):	0.702 g/cm ³ (5.858 lbs/gal)
· Relative density	Not determined.

Printing date 06/27/2023

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

		(Contd. of page 5)
· Vapor density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/v	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	94.8 %	
Solids content:	0.2 %	

10 Stability and reactivity

· Reactivity No further relevant information available.

- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- \cdot Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

 \cdot Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%

Oral LD50 >5000 mg/kg (Rat)

Dermal LD50 >2000 mg/kg (Rabbit)

Inhalative LC50 (4h) 4951 mg/l (Rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· Carcinogenic categories

IARC (International Agency for Research on Cancer)	
140-11-4 benzyl acetate	3
5989-27-5 (R)-p-mentha-1,8-diene	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

(Contd. on page 7)

Printing date 06/27/2023

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

(Contd. of page 6)

12 Ecological information

· Toxicity

• Aquatic toxicity:

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%

EL0 (48h) 1000 mg/l (Daphnia magna)

EL0 (72h) 1000 mg/l (Pseudokirchneriella subcapitata)

- LL0 (96h) 1000 mg/l (Oncorhynchus mykiss)
- · Persistence and degradability Not easily biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
DOT, ADR, ADN, IMDG, IATA	UN1950	
UN proper shipping name		
DOT	Aerosols, flammable	
ADR, ADN	UN1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
· Transport hazard class(es) · DOT		
· Class	2.1 Gases	

US -

Printing date 06/27/2023

Reviewed on 06/27/2023

	(Contd. of page
ADR	
Class Label	2 5F Gases 2.1
ADN ADN/R Class:	2 5F
IMDG, IATA	
Class Label	2.1 Gases 2.1
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code EMS Number: Stowage Code Segregation Code	 Warning: Gases e): - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

(Contd. on page 9)

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

(Contd. of page 8)

Safety, health and environmental regulations/legislation specific for the substance Sara	e or mixture
Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act):	
106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)	ACTIVI
74-98-6 propane	ACTIVI
1338-43-8 Sorbitanoleate	ACTIVI
75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	ACTIVI
· Hazardous Air Pollutants	
101-84-8 diphenyl ether	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Cancerogenity categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value)	
140-11-4 benzyl acetate	A
MAK (German Maximum Workplace Concentration)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
National regulations:	
Disturbance regulations:	
Class Share in %	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Classification according to Regulation (EC) No 1272/2008

Fysiske og kjemiske egenskaper: Klassifiseringen er basert på resultatene av blandingene som er testet. Helsefarer, Miljøfarer: Metoden for klassifisering av blandinger basert på blandingens bestanddeler (sumformel).

(Contd. on page 10)

*

Printing date 06/27/2023

Reviewed on 06/27/2023

Trade name: Muc-Off Motorcycle Chain Cleaner

(Conte	d. of page
Department issuing SDS: Research & Development	
Contact: info@muc-off.com	
Date of preparation / last revision 06/27/2023	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the	;
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flammable Aerosols 1: Aerosols – Category 1	
Gases under Pressure - Liquefied gas: Gases under pressure – Liquefied gas	
Aspiration Hazard 1: Aspiration hazard – Category 1	