

Printing date 09/19/2023 Reviewed on 09/19/2023

# 1 Identification

- · Product identifier
- · Trade name: Muc-Off Bike Protect
- · Article number: 909CA
- · Application of the substance / the mixture Lubricant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Muc-Off Ltd

UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW

EU- Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork, Ireland,

T23 AT2F

Tel: +44(0)1202 307790 Email: info@muc-off.com

- · Information department: Research & Development/E-mail:info@muc-off.com
- · Emergency telephone number: Health Canada toll-free number, 1-844 POISON-X, or 1-844-764-7669

# 2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Aerosols - Category 1

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



GHS04 Gas cylinder

Gases Under Pressure - Liquefied Gas H280

Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Aspiration Hazard - Category 1

H304

May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02

GHS04

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

· Hazard statements

H222-H229 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Printing date 09/19/2023 Reviewed on 09/19/2023

#### Trade name: Muc-Off Bike Protect

	(Contd. of page	1)
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves / eye protection.	
P312	Call a poison center/doctor if you feel unwell.	
P403	Store in a well-ventilated place.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations	3.

# 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description: Active substance with propellant

· Dangerous components:			
	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	50-<75% w/w *	
74-98-6	propane	2.5-<10% w/w *	
106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)	2.5-<10% w/w *	
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	1-<2.5% w/w *	

<sup>\*</sup> Actual concentration ranges are withheld as a trade secret.

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 3)

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

(Contd. of page 2)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility:
- Observe official regulations on storing packagings with pressurized containers.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### 74-98-6 propane

EL Simple asphyxiant; EX

EV TWA: 1,000 ppm

revoked as of 01/01/18

# 106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

EL STEL: 1000 ppm

EX

EV TWA: 800 ppm

revoked as of 01/01/18

# 75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)

EL STEL: 1000 ppm

EX

EV TWA: 800 ppm

revoked as of 01/01/18

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

General ventilation

# · Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

#### · Protection of hands:

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5 \text{ mm}$ 

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:

Safety glasses



Tightly sealed goggles

# · Body protection:

Use protective suit.

Fully skin-covering antistatic, chemical- and oil-resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

#### · Limitation and supervision of exposure into the environment

Use an appropriate container to prevent environmental contamination.

# 9 Physical and chemical properties

Information on basic physical and chemical properties		
· General Information Color:	Colorless	
· Odor:	Characteristic	
Odor threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic.	
· Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	-44.5 °C	
· Flash point:	-97 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Auto igniting:	>200 °C	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
Lower:	0.5 Vol %	

(Contd. on page 5)

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

		(Contd. of page
Upper:	10.9 Vol %	
· Vapor pressure at 20 °C:	3200 hPa	
· Density at 20 °C:	0.752 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Organic solvents:	20.0 %	
Solids content:	0.6 %	

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	LD/LC50 values that are relevant for classification:  Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Hydrocar			
Oral	LD50	>5000 mg/kg (Rat)	
	NOAEL	100-5000 mg/kg/d (Rat)	
Dermal	LD50	>3160 mg/kg (Rabbit)	
Inhalative	LC50 (4h)	>5000 mg/l (Rat)	

- Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
91-64-5 Coumarin	3

# · NTP (National Toxicology Program)

None of the ingredients is listed.

CA

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

(Contd. of page 5)

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics

NOELR (72h) 3198 mg/l (Skeletonema costatum)

- · Persistence and degradability Not easily biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

# 14 Transport information

- · UN-Number
- · DOT/TDG, ADR, ADN, IMDG, IATA UN1950
- · UN proper shipping name
- DOT/TDG
   Aerosols, flammable
   ADR, ADN
   UN1950 Aerosols
   IMDG
   AEROSOLS
- · IATA AEROSOLS, flammable
- · Transport hazard class(es)
- · DOT/TDG (Transport dangerous goods):



• Class 2.1 Gases • Label 2.1

· ADR



· Class 2 5F Gases

(Contd. on page 7)

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

	(Contd. of page
· Label	2.1
· ADN · ADN/R Class:	2 5F
· IMDG, IATA	
·Class	2.1 Gases
· Label	2.1
· Packing group · DOT/TDG, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases
· Hazard identification number (Kemler c	
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre:
	Category A. For AEROSOLS with a capacity above 1 litre:
	Category B. For WASTE AEROSOLS: Category C, Clear o
	living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of
	Not applicable.
· Transport/Additional information:	
· ADR	C 1 F0
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

(Contd. on page 8)

(Contd. of page 7)

# Safety Data Sheet according to HPR, Schedule 1

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

	(Col	itu. 01 page 7)
· TSCA (Toxic Substances Control Act):		
74-98-6	propane	ACTIVE
	(	ACTIVE
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic <0.1% Benzene (IP 346 < 3%)	ACTIVE
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	ACTIVE

### · MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

#### · CANADIAN SUSTANCE LISTINGS

· CANADIA	· CANADIAN DOMESTIC SUSTANCES LIST (DSL)		
74-98-6	propane		
106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)		
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic <0.1% Benzene (IP 346 < 3%)		
75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)		
91-64-5	Coumarin		
120-57-0	piperonal		
121-33-5	vanillin		
123-11-5	p-Methoxybenzaldehyde		
120-51-4	Benzyl benzoate		
	2.5-thiophenediylbis(5-tert-butyl-1,3-benzoxazol)		
104-21-2	p-Anisyl acetate		
118-58-1	benzyl salicylate		
. CANADIAN DISCLOSUDE LIST (0.10/.)			

#### · CANADIAN DISCLOSURE LIST (0.1%)

None of the ingredients is listed.

#### · CANADIAN DISCLOSURE LIST (1%)

106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

- · National regulations:
- · Disturbance regulations:

Class	Share in %
NK	10-<25

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Classification according to Regulation (EC) No 1272/2008

Fysiske og kjemiske egenskaper: Klassifiseringen er basert på resultatene av blandingene som er testet. Helsefarer, Miljøfarer: Metoden for klassifisering av blandinger basert på blandingens bestanddeler (sumformel).

- · Contact: info@muc-off.com
- · Date of the latest revision of the safety data sheet 09/19/2023
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 9)

Printing date 09/19/2023 Reviewed on 09/19/2023

Trade name: Muc-Off Bike Protect

(Contd. of page 8)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

C۸