SAFETY DATA SHEET

Primary Chaincase Lubricant



Section 1. Identification Product identifier : Primary Chaincase Lubricant Product code : 301830150033 Other means of : Not available. identification . Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Lubricating Oil	
Uses advised against	Reason

Supplier's details : Calumet Branded Products, LLC 2780 Waterfront Pkwy E. Drive Suite 200 Indianapolis, IN 46214 USA Technical Services:317-328-5660	
--	--

24hr. CHEMTREC :	24 hr. CHEMTREC 1-800-424-9300 / International 1-703-527-3887

1-800-424-9300 / International 1-703-527-3887

Section 2. Hazard identification

Classification of the substance or mixture	:	AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3
GHS label elements		
Signal word	:	No signal word.
Hazard statements	:	Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	:	Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	:	Avoid release to the environment.
Response	1	Not applicable.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 3. Composition/information on ingredients

Substance/mixture	
Other means of	
identification	

- : Mixture
- : Not available.

1/14

Section 3. Composition/information on ingredients

Ingredient name	Synonyms	% (w/w)	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	Baseoil - unspecified; Distillates, petroleum, hydrotreated heavy paraffinic; Mineral oil, petroleum distillates, hydrotreated heavy paraffinic; Distillates (petroleum), hydro-treated heavy paraffinic; Paraffin oil; HYDROTREATED HEAVY PARAFFINIC DISTILLATE; DISTILLATES (PETROLEUM) HYDROFVLD; Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified	≥60 - ≤80	64742-54-7
Distillates (petroleum), hydrotreated heavy paraffinic	Baseoil - unspecified; Distillates, petroleum, hydrotreated heavy paraffinic; Mineral oil, petroleum distillates, hydrotreated heavy paraffinic; Distillates (petroleum), hydro-treated heavy paraffinic; Paraffin oil; HYDROTREATED HEAVY PARAFFINIC DISTILLATE; DISTILLATES (PETROLEUM) HYDROFVLD; Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified	≥10 - ≤30	64742-54-7
Distillates (petroleum), solvent- dewaxed heavy paraffinic	Baseoil - unspecified; Distillates, petroleum, solvent dewaxed heavy paraffinic; Mineral oil, petroleum distillates, solvent-dewaxed heavy paraffinic; Paraffin oil; Distillates, petroleum, solvent-dewaxed heavy paraffinic; Distillate (Pet.) solvent- dewaxed heavy paraffinic; SOLVENT REFINED PARAFFINIC MINERAL OIL; OILS, PARAFFINIC, HEAVY, SOLVENT DEWAXED; Solvent dewaxed heavy paraffinic petroleum oil; PARAFFINIC PETROLEUM DISTILLATES; Distillates (petroleum), solvent- dewaxed heavy paraffinic, Baseoil - unspecified	≥5 - ≤10	64742-65-0
Distillates (petroleum), solvent- dewaxed light paraffinic	Baseoil - unspecified; Distillates, petroleum, solvent dewaxed light paraffinic; Mineral oil, petroleum distillates, solvent-dewaxed light paraffinic; Solvent-dewaxed light paraffinic distillates (petroleum); Distillate (petroleum), solvent dewaxed light paraffinic distillate; Distillates, petroleum, solvent- dewaxed light paraffinic; Distillates (petroleum), solvent dewaxed light paraffinic; Distillates (petroleum), solvent-dewaxed light paraffinic, Baseoil - unspecified; Petroleum distillates, solvent dewaxed light paraffinic;	≥1 - ≤5	64742-56-9
Distillates (petroleum), hydrotreated	Baseoil - unspecified; Distillates,	≥1 - ≤5	64742-55-8

Section 3. Composition/information on ingredients

ight paraffinic	petroleum, hydrotreated light		
	paraffinic; Mineral oil, petroleum		
	distillates, hydrotreated light		
	paraffinic; Mineral oil, petroleum		
	distillates, hydrotreated (mild) light		
	paraffinic; Distillates (petroleum),		
	hydro-treated light paraffinic; Paraffin		
	oil; DISTILLATES (PETROLEUM)		
	HYDROTREATED LIGHT		
	PARAFFINIC; DISTILLATES,		
	PARAFFINIC; ALIPHATIC		
	HYDROCARBON, SULFURIZED;		
	Distillates (petroleum), hydrotreated		
	light paraffinic, Baseoil - unspecified		
Distillates (petroleum), hydrotreated	Baseoil - unspecified; Distillates,	≥1 - ≤5	64742-52-5
eavy naphthenic	petroleum, hydrotreated heavy		
	naphthenic; Hydrotreated heavy		
	naphthenic distillate, solvent extract,		
	petroleum; Mineral oil, petroleum		
	distillates, hydrotreated heavy		
	naphthenic; Mineral oil, petroleum		
	distillates, hydrotreated (severe)		
	heavy naphthenic; Distillates		
	(petroleum), hydro-treated heavy		
	naphthenic; Hydrotreated heavy		
	naphthenic distillate solvent extract		
	(petroleum); OILS, MINERAL,		
	HEAVY NAPHTHENIC,		
	HYDROTREATED; OILS,		
	NAPHTHENIC, HYDROGENATED;		
	SEVERELY SOLVENT REFINED		
	HEAVY PARAFFINIC DISTILLATES;		
	HYDROTREATED LIGHT		
	PETROLEUM DISTILLATE		
tinc bis(dipentyldithiocarbamate)	Zinc, bis(N,N-	≥1 - ≤5	15337-18-5
	dipentylcarbamodithioatokappa.S,.		
	kappa.S')-, (T-4)-; Zinc, bis		
	(dipentylcarbamodithioato-S,S')-, (ß-		
	4)-; Zinc, bis		
	(dipentylcarbamodithioato-S,S')-, (T-		
	4)-; Zinc, bis		
	(dipentylcarbamodithioatokappa.S,		
	(appendicarbamodifficatokappa.c, kappa.c), kappa.S')-, (T-4)-; ZINC		
	DIAMYLDITHIOCARBAMATE; Zinc		
	N,N-dipentylcarbamodithioate; Zinc		
	N-diamyldithiocarbamate; BIS		
	(DIPENTYLCARBAMODITHIOATO-		
	S,S')-ZINC; ZINC, BIS		
	(DIPENTYLCARBAMODITHIOATE		
	S,S); ZINC,BIS		
	(DIPENTYLCARBAMO		
	DITHIONATE S,S); Zinc,bis		
	(dipentylcarbamodithioatoS,S')		
mines, C12-14-tert-alkyl, compds.	Amines, C12-14-tert-alkyl,	≥0.1 - ≤1	68911-68-2
	compounds with 2(3H)-	_0.11	00011-00-2
(ith 2(3H)_hanzathiazalathiana			
vith 2(3H)-benzothiazolethione		1	
/ith 2(3H)-benzothiazolethione	benzothiazolethione; (C12-14) tert-		
vith 2(3H)-benzothiazolethione	Alkylamines, compound with 2(3H)-		
vith 2(3H)-benzothiazolethione	Alkylamines, compound with 2(3H)- benzothiazolethione; C12-14-tert-		
/ith 2(3H)-benzothiazolethione	Alkylamines, compound with 2(3H)- benzothiazolethione; C12-14-tert- Alkylamines, compd. with 2(3H)-		
vith 2(3H)-benzothiazolethione	Alkylamines, compound with 2(3H)- benzothiazolethione; C12-14-tert-		

Section 3. Composition/information on ingredients

(C=12-14) amines compds. with 2- (3H) benzothiazolethione; AMINES, C12-14 TERT ALKYL, COMPOUNDS WITH 2(3-H) BENZOTHIAZOLETHION	
--	--

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	 Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	 Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms/effects, acute and delayed

Potential acute health e	ffects	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/sy	<u>imptoms</u>	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	: No specific treatment.	

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

4/14

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	Precautions for safe handling					
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.				
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.				
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.				

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral]
heavy paraffinic	8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist
	15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral]
heavy paraffinic	8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist
	15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral]
dewaxed heavy paraffinic	8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist
	15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral]
dewaxed light paraffinic	8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist
	15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral]
light paraffinic	8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist
	15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral]
heavy naphthenic	8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist
	15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist

Biological exposure indices

No exposure indices known.

Appropriate engineering controls		Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	Liquid.				
Color	1	Red.				
Odor	1	Characteristic.				
Odor threshold	1	Not available.				
рН	1	Not available.				
Melting point/freezing point	1	Not available.				
Boiling point, initial boiling point, and boiling range	:	Not available.				
Flash point	:	Open cup: 232.22°C	(450°F) [Clevelar	nd]	
Evaporation rate	:	Not available.				
Flammability	1	Not available.				
Lower and upper explosion limit/flammability limit	:	Not available.				
Vapor pressure	:		Vapor	Pressu	re at 20°C	Va
		Ingredient name	mm Hg	kPa	Method	mm Hg
		Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191	

Relative vapor density

: Not available.

Date of issue/Date of revision

7/14

Method

Vapor pressure at 50°C

kPa

Section 9. Physical and chemical properties and safety characteristics

Relative density	1	0.8691				
Solubility(ies)	:	Media	Result			
		cold water hot water	Not soluble Not soluble			
Solubility in water	:	Not available.				
Partition coefficient: n- octanol/water	:	Not applicable.	lot applicable.			
Auto-ignition temperature	:	Not available.	lot available.			
Decomposition temperature	:	lot available.				
Viscosity	:	inematic (40°C (104°F)): 57.59 mm²/s (57.59 cSt)				
Flow time (ISO 2431)	:	Not available.	ot available.			
Pour point	:	-45°C (-49°F)	45°C (-49°F)			
Particle characteristics						
Median particle size	:	Not applicable.				

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: No specific data.	
Incompatible materials	: No specific data.	
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), solvent-dewaxed light paraffinic	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum),	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
ate of issue/Date of revision	: 08/25/2023 Date of previous iss	ue :N	lo previous validation	Version :1

Section 11. Toxicological information

	•			
hydrotreated light paraffinic				
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum),	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
hydrotreated heavy				
naphthenic				
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
zinc bis	LD50 Dermal	Rabbit	>16000 mg/kg	-
(dipentyldithiocarbamate)				
	LD50 Oral	Rat	>2000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
zinc bis (dipentyldithiocarbamate) Amines, C12-14-tert-alkyl, compds. with 2(3H)- benzothiazolethione	skin skin	Mouse Guinea pig	Not sensitizing Sensitizing

Mutagenicity

Product/ingredient name	Test	Experiment	Result
zinc bis (dipentyldithiocarbamate)	OECD 471 Bacterial Reverse Mutation Test OECD 487 <i>In vitro</i> Micronucleus Test	Experiment: In vitro Subject: Bacteria Experiment: In vitro Subject: Mammalian-Human	Negative Negative

Carcinogenicity

Not available.

Classification

Product/ingredient name	IARC	NTP	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	A4
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	A4
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	A4
Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	A4
Distillates (petroleum), hydrotreated light paraffinic	-	-	A4
Distillates (petroleum), hydrotreated heavy naphthenic	-	-	A4

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
zinc bis (dipentyldithiocarbamate)	Equivocal	Equivocal	Equivocal		Oral: 250 mg/kg	-

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

9/14

Section 11. Toxicological information

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
<u>Long term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health effe	<u>ects</u>	
Not available.		
General	: No known significant effects or critical hazards.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Reproductive toxicity	: No known significant effects or critical hazards.	

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Primary Chaincase Lubricant	215528.2	2562.6	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	N/A	2500	N/A	N/A	5.7
Distillates (petroleum), hydrotreated heavy paraffinic	N/A	2500	N/A	N/A	5.7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed light paraffinic	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light paraffinic	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy naphthenic	N/A	2500	N/A	N/A	5.7
zinc bis(dipentyldithiocarbamate)	2500	N/A	N/A	N/A	N/A
Date of issue/Date of revision : 08/25/2023 Date of	previous issue	: No p	revious validation	Version	:1 10/14

Section 11. Toxicological information

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy paraffinio	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Chronic NOEL >1 mg/l	Daphnia	21 days
Distillates (petroleum), hydrotreated heavy paraffinio	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute IC50 >100 mg/l	Algae	72 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Chronic NOEL >1 mg/l	Daphnia	21 days
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute LC50 4.5 mg/l	Fish	96 hours
Distillates (petroleum), hydrotreated light paraffinic	Acute EC50 >100 mg/l	Algae	72 hours
, , , , , , , , , , , , , , , , , , , ,	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Distillates (petroleum), hydrotreated heavy naphthenic	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Crustaceans	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Amines, C12-14-tert-alkyl, compds. with 2(3H)- benzothiazolethione	Acute EC50 0.86 mg/l	Algae	72 hours
	Acute EC50 2.2 mg/l	Daphnia	48 hours
	Acute NOEC 0.1 mg/l	Algae	72 hours
	Acute NOEC 0.8 mg/l	Daphnia	48 hours

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
zinc bis (dipentyldithiocarbamate)	OECD 301B Ready Biodegradability - CO ₂ Evolution Test	21 % - Not readily - 28 days	-	-
Amines, C12-14-tert-alkyl, compds. with 2(3H)- benzothiazolethione	OECD 301D Ready Biodegradability - Closed Bottle Test	42.57 % - Not readily - 28 days	-	-

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum),	-	-	Inherent
hydrotreated heavy paraffinic			
Distillates (petroleum),	-	-	Not readily
hydrotreated heavy paraffinic			
Distillates (petroleum),	-	-	Inherent
hydrotreated light paraffinic			
Distillates (petroleum),	-	-	Inherent
hydrotreated heavy			
naphthenic			
zinc bis	-	-	Not readily
(dipentyldithiocarbamate)			
Amines, C12-14-tert-alkyl,	-	-	Not readily
compds. with 2(3H)-			
benzothiazolethione			

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>6	-	High
Distillates (petroleum), hydrotreated heavy paraffinic	>6	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	2 to 6	-	High
Distillates (petroleum), hydrotreated light paraffinic	>6	-	High

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue/Date of revision	: 08/25/2023	Date of previous issue	: No previous validation	Version	:1	12/14
--------------------------------	--------------	------------------------	--------------------------	---------	----	-------

Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

<u>Canadian lists</u>		
Canadian NPRI	The following components are listed: zinc (and its compounds)	
CEPA Toxic substances	None of the components are listed.	
Inventory list		
Australia	All components are listed or exempted.	
Canada	All components are listed or exempted.	
China	All components are listed or exempted.	
Eurasian Economic Union	Russian Federation inventory: All components are listed or exempted.	
New Zealand	All components are listed or exempted.	
Philippines	All components are listed or exempted.	
Republic of Korea	All components are listed or exempted.	
Taiwan	All components are listed or exempted.	
Thailand	Not determined.	
Turkey	Not determined.	
United States	All components are active or exempted.	
Viet Nam	All components are listed or exempted.	

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 08/25/2023
Date of previous issue	: No previous validation
Version	: 1
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

V Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.